






		Conditions	
cell type:	NiMH		
cell size:	AAA		
nominal voltage:	1.2 V		
max. charge voltage:	1.5 V	at standard charge (0.1C / 20°C)	
capacity			
nominal:	1100 mAh	discharge at 0.2C	
minimum:	1050 mAh	discharge at 0.2C	
	950 mAh	discharge at 1C	
		1.0V end discharge voltage	
		ta: 20°C	
max. continuous discharge current:	3000 mA	ta: 0...45°C	
charge		current	time
standard charge:		105 mA	14....16hrs
quick charge:		315 mA	4hrs
fast charge:		1050 mA	1.1hrs
recommended charge termination control parameters:	0...5 mV	-ΔV (-delta V)	
	0.8...1 °C	temperature rise per minute	
	45...50 °C	TCO (temperature cut off)	
trickle charge current:	10...30 mA	(recommended)	
continuous overcharge: (less than 1 year)	≤ 50 mA	no conspicuous deformation no leakage	
internal resistance: (impedance)	≤ 40 mΩ	at 1KHz battery fully charged	
life expectancy:	≥ 500 cycles	acc. IEC standard	
self discharge			
charge retention after 360 days storage at 20°C:	≥ 50 %	of minimal battery capacity; at 0.2C discharge to EV 1.0V	
subsequent capacity:	≥ 525 mAh		
initial capacity:	≥ 750 mAh	within 30 days after delivery discharge at 0.2C	
ambient temperature range:	0...45 °C	standard charge	
	10...40 °C	fast charge	
	- 20...65 °C	discharge	
	- 20...50 °C	storage (≤1month)	
	- 20...40 °C	storage (≤3months)	
	- 20...30 °C	storage (≤12months)	

QCT1:	20/1000/40
QCT2:	30/950/50

mechanical specifications		
cell dimensions		
diameter d1 (incl. label):	10.5 - 0.7	mm
diameter d1 (bare cell):	10.3 - 0.7	mm
diameter d2:	max. 3.8	mm
height h1:	44.5 - 1.5	mm
height h2:	min. 0.8	mm
weight:	13.5 ± 2	g



Diagrams



	ANSMANN Specifications for model:	NiMH Battery
		AAA - 1100mAh low self discharge
	data sheet no. / part no.	
	s.n.	701372
author / date	TG / 18.06.2024	