

**battery type:** Alkaline Manganese (Mercury free)  
**battery size:** IEC: LR03; JIS: AM-4; ANSI: 24A; MN2400; AAA; Micro  
**chemical system:** Zn / KOH-H<sub>2</sub>O / MnO<sub>2</sub>

**nominal voltage:** 1.5 V  
**open circuit voltage:** 1.57...1.62 V new battery  
 1.55...1.62 V after 1 year storage at 20°C

**capacity rated:** 1300 mAh all measurements at 20°C ambient  
 discharge at 10mA load; 24h/d  
 End Voltage (EV): 0.8V  
 1200 mAh discharge at 75Ω resistive load; 24h/d  
 End Voltage (EV): 0.8V

**minimum:** 18 h at 20ohms constant resistance discharge  
 End Voltage (EV): 0.9V  
 37 min at 500mA constant current discharge  
 End Voltage (EV): 0.9V

**typical service output**

Load	20Ω	600mA	600mA	5.1Ω	10Ω	24Ω	75Ω	
Test mode	24h/d	24h/d	10s/m, 1h/d	4m/h,8h/d	1h/d	15s/m,8h/d	4h/d	
end voltage	0.9V	0.9V	0.9V	0.9V	0.9V	1.0v	0.9V	
Initial	M.A.D	18.0 h	37.0 m	380 cycles	225.0m	8.2h	19.5 h	71.0 h
	Normal	19.0 h	45.0 m	440 cycles	245.0m	8.7h	21.0 h	74.0 h
After 1 year	M.A.D	17.0 h	30.0 m	340 cycles	210.0 m	7.9h	19.0 h	69.0 h
	Normal	18.0 h	38.0 m	380 cycles	235.0 m	8.4h	20.5 h	73.0 h

m: minute h: hour d: day

**internal resistance:** ≤ 0.3 Ω at 1kHz, sine wave measurement  
 (new battery) according to IEC 896-2

**shelf life:** 7 years under proper storage conditions


**leakage resistance**  
 over discharge: no leakage 20ohms continuous discharge for 48h; ta: 20°C; RH: 60±15%  
 high temperature: no leakage store 20days at ta: 60°C; RH:90±5%

**ambient temperature range:** - 10...50 °C

recommended storage conditions: 5...25 °C ambient temperature  
 45...75 % rel. humidity

**mechanical specifications**

cell dimensions  
 diameter d1: 10.4 - 0.5 mm  
 diameter d2: 3.6 - 0.4 mm  
 height h1: 44.4 - 0.6 mm  
 height h2: 1.2 - 0.35 mm  
 weight: 12 ± 1.5 g



	<b>ANSMANN Specifications for model:</b>	<b>Premium Alkaline Battery AAA - size</b>
	data sheet no. / part no.	
	s.n.	701381
	author / date	TG / 28.06.2019